

- **Model:** HXLBQ-DTA345
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2515~2615MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2565MHz	
● Pass Band Frequency	2515 ~ 2615MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤1.0dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Attenuation	≥40dB @ DC ~ 2500MHz	≥40dB @ 2630 ~ 5000MHz
● Impedance	50 Ohms	
● Power Handling	30W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: H59 Copper, Plated ternary alloy Other screw: Stainless Steel
● Dimensions	92*92*21mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

