

- **Model:** HXLBQ-DTA394
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2305~2315MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2310MHz	
● Pass Band Frequency	2305 ~ 2315MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band VSWR	≤1.22:1	
● Stop Band Rejection	≥50dB @ DC ~ 2265MHz	≥50dB @ 2355 ~ 4500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	100*68*26mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

