

- **Model:** HXLBQ-DTA443
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2496~2570MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2533MHz	
● Pass Band Frequency	2496 ~ 2570MHz	
● Pass Band Insertion Loss	≤1.2dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band VSWR	≤1.22:1	
● Stop Band Rejection	≥50dB @ DC ~ 2466MHz	≥50dB @ 2600 ~ 6000MHz
● Impedance	50 Ohms	
● Power	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	120*62*26mm	
● Net weight	0.285 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

