

- **Model: HXLBQ-DTA453**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 867~870MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	868.5MHz	
● Pass Band Frequency	867 ~ 870MHz	
● Pass Band Insertion Loss	≤2.0dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥30dB @ DC ~ 862MHz	≥30dB @ 875 ~ 3500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-20°C ~ +60°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	95*65*41mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

