

- **Model:** HXLBQ-DTA488
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 3425~3575MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	3500MHz	
● Pass Band Frequency	3425 ~ 3575MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.7dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥40dB @ DC ~ 3350MHz	≥40dB @ 3650 ~ 7000MHz
● Impedance	50 Ohms	
● Power	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: H62 Copper alloy Cover: H62 Copper alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	100*19*16mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

