

- **Model:** HXLBQ-DTA492
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 4000~4050MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	4025MHz	
● Pass Band Frequency	4000 ~ 4050MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.2dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Attenuation	≥80dB @ DC ~ 3890MHz	≥40dB @ 4100 ~ 4160MHz
	≥40dB @ 3890 ~ 3950MHz	≥80dB @ 4160 ~ 9000MHz
● Impedance	50 Ohms	
● Power Handling	10W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy	Connectors: Stainless Steel
	Cover: LY12 Aluminum alloy	Other screw: Stainless Steel
	Tuning screw: H62 Copper alloy	
● Dimensions	110*21*17mm	
● Net weight	TBD	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)		

