

- **Model: HXLBQ-DTA601**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2100~2170MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	2135MHz	
● Pass Band Frequency	2100 ~ 2170MHz	
● Pass Band Insertion Loss	≤1.0dB	
● Pass Band Ripple	≤0.5dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥60dB @ DC ~ 2050MHz	≥60dB @ 2220 ~ 4500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	141*73*26mm	
● Net weight	0.36 KG	

● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

