

- **Model: HXLBQ-DTA613**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 850~950MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters	
● Center Frequency(F0)	900MHz	
● Pass Band Frequency	850 ~ 950MHz	
● Pass Band Insertion Loss	≤0.6dB	
● Pass Band Ripple	≤0.3dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥60dB @ DC ~ 750MHz	≥65dB @ 1050 ~ 3800MHz
● Impedance	50 Ohms	
● Power	50W Max.	
● Connectors	N-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Resonant column: H59 Copper alloy Cover: LY12 Aluminum alloy Connectors: H59 Copper, Plated ternary alloy Tuning screw: H62 Copper alloy Other screw: Stainless Steel	
● Dimensions	141*40*30mm	
● Net weight	TBD	

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

