

- **Model: HXLBQ-DTA627**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1559~1590MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1574.5MHz	
● Pass Band Frequency	1559 ~ 1590MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.7dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥50dB @ DC ~ 1544MHz	≥50dB @ 1605 ~ 4500MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	120*62*31mm	
● Net weight	0.36 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

