

- **Model: HXLBQ-DTA647**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1165~1187MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	1176MHz	
● Pass Band Frequency	1165 ~ 1187MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.7dB	
● Pass Band Return Loss	≥20dB	
● Stop Band Rejection	≥80dB @ DC ~ 1115MHz	≥80dB @ 1237 ~ 3000MHz
● Impedance	50 Ohms	
● Power Handling	20W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Resonant column: H59 Copper alloy Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	120*62*31mm	
● Net weight	0.36 KG	
●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)		

