

- **Model: HXLBQ-DTA778**
- **Product Name: Comb Band Pass Filter**
- **Frequency: 2500~3750MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	3125MHz
● Pass Band Frequency	2500 ~ 3750MHz **
● Pass Band Insertion Loss	≤1.2dB
● Pass Band Ripple	≤0.8dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥80dB @ DC ~ 2100MHz ≥60dB @ 3900 ~ 3950MHz ≥50dB @ 2100 ~ 2250MHz ≥80dB @ 3950 ~ 8000MHz ≥35dB @ 2250 ~ 2350MHz
● Impedance	50 Ohms
● Power Handling	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Material	Housing: 6061 Aluminum alloy Connectors: Stainless Steel Cover: LY12 Aluminum alloy Other screw: Stainless Steel Tuning screw: H62 Copper alloy
● Dimensions	160*24*21mm
● Net weight	TBD

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

