

- **Model:** HXLBQ-DTA1057
- **Product Name:** Interdigital Band Pass Filter
- **Frequency:** 1950~2500MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	2225MHz	
● Pass Band Frequency	1950 ~ 2500MHz **	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.9dB	
● Pass Band Return Loss	≥14dB	
● Stop Band Rejection	≥50dB @ DC ~ 1770MHz	≥50dB @ 2680 ~ 4000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Material	Housing: 6061 Aluminum alloy Cover: LY12 Aluminum alloy Tuning screw: H62 Copper alloy	Connectors: Stainless Steel Other screw: Stainless Steel
● Dimensions	90*38*11mm	
● Net weight	TBD	

** The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

