

- **Model:** HXLBQ-DTA1158
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 7100~7180MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet		
Item	Parameters	
● Center Frequency(F0)	7140MHz	
● Pass Band Frequency	7100 ~ 7180MHz	
● Pass Band Insertion Loss	≤1.5dB	
● Pass Band Ripple	≤0.8dB	
● Pass Band Return Loss	≥23dB	
● Stop Band Rejection	≥80dB @ DC ~ 6650MHz	≥7.0dB @ 7230 ~ 7500MHz
	≥50dB @ 6650 ~ 6800MHz	≥80dB @ 7500 ~ 25000MHz
● Impedance	50 Ohms	
● Power Handling	5.0W Max.	
● Connectors	SMA-Female	
● Surface Finish	Painted Black	
● Temperature Range	-30°C ~ +70°C	
● Dimensions	70*16*9mm	
● Net weight	0.068 KG	

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

● **Material**

- Housing: H62 Copper alloy
- Connectors: Stainless Steel
- Cover: H62 Copper alloy
- Other screw: Stainless Steel
- Tuning screw: H62 Copper alloy

