

- **Model: HXLBQ-DTD25**
- **Product Name: Low Pass Filter**
- **Frequency: DC~5.0GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	5.0GHz
● Pass Band Frequency	DC ~ 5.0GHz
● Pass Band Insertion Loss	≤1.0dB @ DC ~ 4.8GHz ≤1.5dB @ 4.8 ~ 5.0GHz
● Pass Band VSWR	≤1.3:1
● Stop Band Attenuation	≥60dB @ 5.58 ~ 15GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.02 KG

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|---------------------------|-------------------------------|
| ◆ Material | ● Housing: Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Dimensions: 31*22*10mm | ● screw: Stainless Steel |

