

- **Model: HXLBQ-DTD48**
- **Product Name: Low Pass Filter**
- **Frequency: DC~16.5GHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	16.5GHz
● Pass Band Frequency	DC ~ 16.5GHz
● Pass Band Insertion Loss	≤1.0dB @ DC ~ 16GHz ≤2.4dB @ 16 ~ 16.5GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥50dB @ 17.5 ~ 23GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.014 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material	<ul style="list-style-type: none"> <li style="width: 50%;">● Housing: Aluminum alloy <li style="width: 50%;">● Connectors: Stainless Steel <li style="width: 50%;">● Dimensions: 21*17*10mm <li style="width: 50%;">● screw: Stainless Steel

