

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA25**
- **Frequency: 5.0~24GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	5.0GHz
● Pass Band Frequency	5.0 ~ 24GHz
● Pass Band Insertion Loss	≤1.5dB @ 5.0 ~ 5.2GHz ≤1.0dB @ 5.2 ~ 24GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥50dB @ DC ~ 4.0GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.015 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material <ul style="list-style-type: none"> ● Housing: Aluminum alloy ● Screw: Stainless Steel 	<ul style="list-style-type: none"> ● Connectors: Stainless Steel ● Dimensions: 23*16*10mm

