

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA58**
- **Frequency: 4.0~20GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

| Technical Data Sheet | |
|---|---|
| Item | Parameters |
| ● Cut Off Frequency | 4.0GHz |
| ● Pass Band Frequency | 4.0 ~ 20GHz |
| ● Pass Band Insertion Loss | ≤2.0dB @ 4.0 ~ 4.2GHz ≤1.0dB @ 4.2 ~ 20GHz |
| ● Pass Band VSWR | ≤1.5:1 |
| ● Stop Band Attenuation | ≥60dB @ DC ~ 3.55GHz |
| ● Impedance | 50 Ohms |
| ● Power Handling | 15W Max. |
| ● Connectors | SMA-Female |
| ● Surface Finish | Guide Oxygen or Painted Black |
| ● Temperature Range | -55°C ~ +85°C |
| ● Net weight | 0.035 KG |
| ● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm) | |
| ◆ Material <ul style="list-style-type: none"> ● Housing: Aluminum alloy ● Screw: Stainless Steel | <ul style="list-style-type: none"> ● Connectors: Stainless Steel ● Dimensions: 39*28*10mm |

