

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA60**
- **Frequency: 4.5~21GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	4.5GHz
● Pass Band Frequency	4.5 ~ 21GHz
● Pass Band Insertion Loss	≤2.0dB @ 4.5 ~ 4.75GHz ≤1.0dB @ 4.75 ~ 21GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥60dB @ DC ~ 3.98GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.03 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material <ul style="list-style-type: none"> ● Housing: Aluminum alloy ● Screw: Stainless Steel 	<ul style="list-style-type: none"> ● Connectors: Stainless Steel ● Dimensions: 36*25*10mm

