

- **Product Name: High Pass Filter**
- **Model: HXLBQ-GTA64**
- **Frequency: 6.5~24GHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ Small Size

Technical Data Sheet	
Item	Parameters
● Cut Off Frequency	6.5GHz
● Pass Band Frequency	6.5 ~ 24GHz
● Pass Band Insertion Loss	≤2.0dB @ 6.5 ~ 6.85GHz ≤1.0dB @ 6.85 ~ 24GHz
● Pass Band VSWR	≤1.5:1
● Stop Band Attenuation	≥60dB @ DC ~ 5.83GHz
● Impedance	50 Ohms
● Power Handling	15W Max.
● Connectors	SMA-Female
● Surface Finish	Guide Oxygen or Painted Black
● Temperature Range	-55°C ~ +85°C
● Net weight	0.02 KG
● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)	
◆ Material <ul style="list-style-type: none"> ● Housing: 6061 Aluminum alloy ● Connectors: Stainless Steel ● Screw: Stainless Steel ● Dimensions: 31*21*10mm 	

