

- **Model: HXLBQ-DTA1113**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1089~1091MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1090MHz
● Pass Band Frequency	1089 ~ 1091MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.3dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥80dB @ DC ~ 1010MHz ≥60dB @ 1141 ~ 1170MHz ≥60dB @ 1010 ~ 1039MHz ≥80dB @ 1170 ~ 5000MHz
● Impedance	50 Ohms
● Power Handling	10W Max.
● Connectors	SMA-Male / SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	0.13 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 100*28*31mm |

