

- **Model: HXLBQ-DTA413**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 1710~1980MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	1845MHz
● Pass Band Frequency	1710 ~ 1980MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.5dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥40dB @ DC ~ 1610MHz      ≥40dB @ 2080 ~ 4000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |                                |
|-------------------|----------------------------------|--------------------------------|
| ● <b>Material</b> | ● Housing: 6061 Aluminum alloy   | ● Connectors: Stainless Steel  |
|                   | ● Cover: LY12 Aluminum alloy     | ● Other screw: Stainless Steel |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 188*42*30mm      |

