- **Model：HXLBQ-DTA283**
- **Product Name：Cavity Band Pass Filter**
- **Frequency：6700~6900MHz**

★High Stop Band Rejection
★Low Pass Band Insertion Loss
★Customizable Design
★High Reliability

Technical Data Sheet	
Item	**Parameters**
● Center Frequency(F0)	6800MHz
● Pass Band Frequency	6700 ~ 6900MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥30dB @ DC ~ 6600MHz ≥30dB @ 7000 ~ 15000MHz
● Impedance	50 Ohms
● Power Handling	5.0W Max
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30℃ ~ +70℃
● Net weight	TBD

Note：The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

●Material	●Housing: 6061 Aluminum alloy	●Connectors: H59 Copper, Plated ternary alloy
	●Cover: LY12 Aluminum alloy	●Other screw: Stainless Steel
	●Tuning screw: H62 Copper alloy	●Dimensions: 90*17*14mm



Tel:+86-029-85450833 FAX:+86-029-85450833 E-mail:sales_hxwb@163.com E-mail: sales@xahxmicrowave.com
http://www.xahxmicrowave.com http://www.hx-microwave.com Add:Yanta District, Xi'an, China