

- **Model:** HXLBQ-DTA300X
- **Product Name:** Interdigital Band Pass Filter
- **Frequency:** 2000~3000MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	2500MHz
● Pass Band Frequency	2000 ~ 3000MHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.5dB
● Pass Band VSWR	≤1.5:1
● Stop Band Rejection	≥40dB @ DC ~ 1850MHz ≥40dB @ 3150 ~ 5000MHz
● Impedance	50 Ohms
● Power	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.065 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | |
|---|--|
| <ul style="list-style-type: none"> ● Material ● Housing: 6061 Aluminum alloy ● Cover: LY12 Aluminum alloy ● Tuning screw: H62 Copper alloy | <ul style="list-style-type: none"> ● Connectors: H59 Copper, Plated ternary alloy ● Other screw: Stainless Steel ● Dimensions: 80*43*11mm |
|---|--|

