

- **Model:** HXLBQ-DTA613
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 850~950MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	900MHz
● Pass Band Frequency	850 ~ 950MHz
● Pass Band Insertion Loss	≤0.6dB
● Pass Band Ripple	≤0.3dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥60dB @ DC ~ 750MHz ≥65dB @ 1050 ~ 3800MHz
● Impedance	50 Ohms
● Power	50W Max.
● Connectors	N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 141*47*30mm |

