

- **Model:** HXLBQ-DTA358X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2088~2098MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	2093MHz
● Pass Band Frequency	2088 ~ 2098MHz
● Pass Band Insertion Loss	≤2.0dB
● Pass Band Ripple	≤0.5dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥40dB @ F0±20MHz (DC ~ 2073MHz , 2113 ~ 5000MHz)
● Impedance	50 Ohms
● Power	10W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|--|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: H59 Copper, Plated ternary alloy |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 100*68*33mm |

