

- **Model:** HXLBQ-DTA468X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 3300~3800MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	3550MHz
● Pass Band Frequency	3300 ~ 3800MHz
● Pass Band Insertion Loss	≤1.8dB
● Pass Band Ripple	≤0.9dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥70dB @ DC ~ 3100MHz ≥70dB @ 4000 ~ 8000MHz
● Impedance	50 Ohms
● Power	100W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|----------------------------------|--------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 170*26*24mm |

