

- **Model:** HXLBQ-DTA466X
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 1850~1950MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1900MHz
● Pass Band Frequency	1850 ~ 1950MHz
● Pass Band Insertion Loss	≤1.3dB
● Pass Band Ripple	≤0.6dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥70dB @ DC ~ 1750MHz ≥70dB @ 2050 ~ 4000MHz
● Impedance	50 Ohms
● Power	100W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: 6061 Aluminum alloy
 - Cover: LY12 Aluminum alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: Stainless Steel
 - Other screw: Stainless Steel
 - Dimensions: 177*42*25mm

