

- **Model: HXLBQ-DTA539**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 3400~3500MHz**
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	3450MHz
● Pass Band Frequency	3400 ~ 3500MHz
● Pass Band Insertion Loss	≤1.7dB
● Pass Band Ripple	≤0.8dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥40dB @ DC ~ 3375MHz      ≥40dB @ 3525 ~ 7000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
- Housing: 6061 Aluminum alloy
- Cover: LY12 Aluminum alloy
- Tuning screw: H62 Copper alloy
- Connectors: Stainless Steel
- Working Environment: Indoor
- Dimensions: 100\*52\*24mm

