



- **Model:** HXLBQ-DTA626
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 923~928MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	925.5MHz
● Pass Band Frequency	923 ~ 928MHz
● Pass Band Insertion Loss	≤3.0dB
● Pass Band Ripple	≤1.0dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥40dB @ DC ~ 908MHz ≥20dB @ 931 ~ 943MHz ≥20dB @ 908 ~ 920MHz ≥40dB @ 943 ~ 2000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	0°C ~ +50°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 95*65*48mm |

