

- **Model:** HXLBQ-DTA739
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 2102~2110MHz
- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	2106MHz
● Pass Band Frequency	2102 ~ 2110MHz
● Pass Band Insertion Loss	≤1.3dB
● Pass Band Ripple	≤0.2dB
● Pass Band Return Loss	≥23dB
● Stop Band Rejection	≥40dB @ DC ~ 2087MHz ≥40dB @ 2125 ~ 6000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-20°C ~ +60°C
● Net weight	0.252 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 100*68*33mm |

