

- **Model: HXLBQ-DTA796**
- **Product Name: Cavity Band Pass Filter**
- **Frequency: 2230~2260MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	2245MHz
● Pass Band Frequency	2230 ~ 2260MHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.4dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥50dB @ DC ~ 2210MHz ≥50dB @ 2280 ~ 6000MHz
● Impedance	50 Ohms
● Power Handling	30W Max.
● Connectors	N-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- | | | |
|-------------------|----------------------------------|-------------------------------|
| ◆ Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Working Environment: Indoor |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 110*57*33mm |

