

- **Model:** HXLBQ-DTA203
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 21.6~22.4GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

**Technical Data Sheet**

Item	Parameters
● Center Frequency(F0)	22GHz
● Pass Band Frequency	21.6~ 22.4GHz
● Pass Band Insertion Loss	≤1.5dB
● Pass Band Ripple	≤0.5dB
● Pass Band VSWR	≤1.3:1
● Stop Band Rejection	≥60dB @ DC ~ 20GHz    ≥60dB @ 24 ~ 40GHz
● Impedance	50 Ohms
● Power Handling	5W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.07 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- |                   |                                  |  |
|-------------------|----------------------------------|--|
| ● <b>Material</b> | ● Housing: H62 Copper alloy      | ● Connectors: H59 Copper, Plated ternary alloy |
|                   | ● Cover: H62 Copper alloy        | ● Other screw: Stainless Steel                 |
|                   | ● Tuning screw: H62 Copper alloy | ● Dimensions: 70*16*12mm                       |

