

- **Model:** HXLBQ-DTA501
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 21~22GHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet

Item	Parameters
● Center Frequency(F0)	21.5GHz
● Pass Band Frequency	21 ~ 22GHz
● Pass Band Insertion Loss	≤1.0dB
● Pass Band Ripple	≤0.25dB
● Pass Band VSWR	≤1.22:1
● Stop Band Rejection	≥80dB @ DC ~ 20GHz ≥80dB @ 23 ~ 40GHz
● Impedance	50 Ohms
● Power Handling	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.07 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm)

- **Material**
 - Housing: H62 Copper alloy
 - Cover: H62 Copper alloy
 - Tuning screw: H62 Copper alloy
 - Connectors: Stainless Steel
 - Working Environment: Indoor
 - Dimensions: 70*16*12mm

