

- **Model:** HXOH-OA46-10DB
- **Product Name:** 10dB Dual Directional Coupler
- **Frequency:** 0.5~18GHz
- ★ Ultra Wide Frequency
- ★ Small Size
- ★ Customizable Design
- ★ High Reliability

| Technical Data Sheet | |
|--|--|
| Item | Parameters |
| ● Frequency Range | 0.5 ~ 18GHz |
| ● Coupling Factor | 10±1.0dB |
| ● Coupling Sensitivity | ≤±1.0dB |
| ● Insertion Loss | ≤2.4dB (Excluding Coupling Loss 0.92dB) |
| ● VSWR | ≤1.5:1 |
| ● Directivity | ≥12dB |
| ● Impedance | 50 Ohms |
| ● Power Handling | Incident: 5W Max. / Reflected: 5W Max. |
| ● Connectors | SMA-Female |
| ● Surface Finish | Painted Black |
| ● Temperature Range | -30°C ~ +70°C |
| ● Net weight | TBD |
| ●Outline Drawing: (Dimensions Unit: mm, Dimensions Tolerance: ±0.5mm) | |
| ● Material | <ul style="list-style-type: none"> ● Housing: 6061 Aluminum alloy ● Connectors: Stainless Steel ● Other screw: Stainless Steel ● Dimensions: 226*21*14mm |

