

- **Model: HXLBQ-DTA930**
- **Product Name: Interdigital Band Pass Filter**
- **Frequency: 1000~2000MHz**

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	1500MHz
● Pass Band Frequency	1000 ~ 2000MHz
● Pass Band Insertion Loss	≤1.2dB
● Pass Band Ripple	≤0.7dB
● Pass Band Return Loss	≥14dB
● Stop Band Rejection	≥60dB @ DC ~ 800MHz ≥60dB @ 2200 ~ 3000MHz
● Impedance	50 Ohms
● Power Handling	5.0W Max.
● Connectors	SMA-Female
● Surface Finish	Painted Black
● Temperature Range	-30°C ~ +70°C
● Net weight	0.106 KG

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|----------------------------------|--------------------------------|
| ● Material | ● Housing: 6061 Aluminum alloy | ● Connectors: Stainless Steel |
| | ● Cover: LY12 Aluminum alloy | ● Other screw: Stainless Steel |
| | ● Tuning screw: H62 Copper alloy | ● Dimensions: 85*61*12mm |

