

- **Model:** HXLBQ-DTA1266
- **Product Name:** Cavity Band Pass Filter
- **Frequency:** 902~928MHz

- ★ High Stop Band Rejection
- ★ Low Pass Band Insertion Loss
- ★ Customizable Design
- ★ High Reliability

Technical Data Sheet	
Item	Parameters
● Center Frequency(F0)	915MHz
● Pass Band Frequency	902 ~ 928MHz
● Pass Band Insertion Loss	≤2.2dB
● Pass Band Ripple	≤1.0dB
● Pass Band Return Loss	≥20dB
● Stop Band Rejection	≥40dB @ DC ~ 894MHz ≥40dB @ 936 ~ 3000MHz
● Impedance	50 Ohms
● Power Handling	20W Max.
● Connectors	SMA-Female
● Surface Finish	Natural conductive oxidation
● Temperature Range	-20°C ~ +60°C
● Net weight	TBD

Note: The actual design bandwidth will be greater than the Pass Band Frequency, and there is no bandwidth limit.

● **Outline Drawing:** (Dimensions Unit: mm, Dimensions Tolerance: ±0.3mm)

- | | | |
|-------------------|---------------------------|--------------------------------|
| ◆ Material | ● Housing: Aluminum alloy | ● Dimensions: 125*65*40mm |
| | ● Cover: Aluminum alloy | ● Natural conductive oxidation |

